



Involute Spiral Face Couplings and Gears: Design Approach and Manufacturing Technique

By Dr. Alexander L. Kapelevich, AKGears, LLC, and Stephen D. Korosec, Koro Industries, Inc.

By presenting spiral face gears with an involute tooth line and an identical tooth profile in the normal section at any given radius, two applications are made possible for such face gears.

INTRODUCTION

Face gears typically have a straight or skewed tooth line and varying tooth profile in normal cross section at different radii from major to minor diameter. These face gears are engaged with spur or helical involute pinions at intersecting or crossed axes.

This paper presents spiral face gears with an involute tooth line and an identical tooth profile in the normal section at any radius. There are two main applications for such face gears. One of them is an alternative solution with certain advantages in performance and fabrication technology to the straight tooth, Hirth, or Curvic flange couplings. Another application is when a face gear is engaged with an involute helical pinion or worm at intersecting or crossed axes.

Potential advantages of spiral face couplings and gears include high power transmission density and highly productive machining of face spiral gears.

This paper describes gear geometry analysis, and design technique of spiral face involute gears with symmetric and asymmetric tooth profiles. It also explains a hobbing method of these gears and tool design specifics, and then illustrates gear and tool design with numerical examples.

GEOMETRY OF INVOLUTE SPIRAL FACE GEARS

Spiral angle at some reference diameter $d > d_b$ is:




Figure 1: Face involute spiral gear; d_b , d_i , d , and d_o are base, minor, reference and major diameters, β is spiral angle at reference diameter, m – module, a – profile (pressure) angle, s – tooth thickness at reference (pitch) line, h_a – tooth addendum, w – whole depth; 1 – tooth flank, 2 – root fillet




Figure 2: Schematics of left hand spiral face gear (black) hobbing with right hand hob (blue); γ – hob lead angle, L – hob length, d_c – hob major diameter; section A-A is tangent to base circle d_b and normal to the gear tooth line; section B-B is parallel to the hob axis, 1 – concave gear tooth flank, 2 – convex flank

$$\beta = \arccos\left(\frac{d_b}{d}\right) \quad (1)$$

Unlike conventional spur or helical gears that have involute tooth flank profiles and straight or helical tooth lines, these spiral face gears have straight tooth

flank profiles in the normal section and the involute tooth line.

Any tangent to the base cylinder diameter d_b is normal to the involute tooth line section of the spiral face gear presenting a straight flank gear rack (see Figure 1, Section A-A). The




Figure 3: Schematics of right hand spiral face gear (black) hobbing with right hand hob (blue)

Number of Teeth	16
Normal Module, mm	6.0
Tooth Addendum, mm	3.7
Whole Depth, mm	8.0
Normal Pressure Angle	45°
Reference Diameter, mm	150.0
Spiral angle at reference diameter, mm	50.2°
Minor Diameter, mm	120.0
Spiral angle at Minor diameter	36.9°
Major Diameter, mm	180.0
Spiral angle at Major diameter	57.8°

Table 1. Experimental involute spiral face coupling gear parameter




Figure 4: Hirth couplings




Figure 5: Curvic couplings

spiral face gear tooth parameters and its root fillet profile can be optimized using Direct Gear Design optimization technique [1] to amplify load capacity by increasing tooth surface durability and minimizing bending stress concentration.

INVOLUTE SPIRAL FACE MACHINING

Since any normal to the involute tooth line section of the spiral face gear presents a straight flank gear rack, a gear hob can be used in manufacturing. Thus, a spiral face gear per this design can be hobbled with the same accuracy as spur and helical gears



Figure 6: Experimental involute spiral face coupling mating flanges and hob (the same hob was used to machine both right and left hand spiral face gears)

utilizing conventional hobbing equipment.

Schematics of spiral face gear hobbing are shown in Figures 2 and 3. Hobbing center distance “a” is:

$$a = \frac{d_b}{2 \cos(\beta)} \times \cos(\beta \pm \gamma) \quad (2)$$

Where the “+” sign if the spiral gear and hob have opposite hands left-right (Figure 2) or right-left, the “-” sign if the spiral gear and hob have the same hands right-right (Figure 3) or left-left.

The normal section of the spiral gear tooth profile is an impression of the hob tooth profile in normal section (Figure 2, Section A-A).

In order to avoid interference and undercut of the concave tooth flank, the minimal gear flank curvature radius r_g must be greater than the maximum hob helical surface radius r_c measured parallel to the hob

axis (see Figure 2, Section B-B) from base diameter d_b to the hob centerline offset by distance “a” or:

$$r_{g \min} > r_{c \max} \quad (3)$$

The minimal gear flank curvature radius r_g min and minor diameter d_i is:

$$r_{g \min} = \frac{d_i}{2} \times \tan \left(\arccos \left(\frac{d_b}{d_i} \right) \right) \quad (4)$$

A profile of the hob helical surface section parallel to its axis presents a complex curve and exact definition of its maximum radius r_c max at a contact point with the concave gear flank is a difficult task. However, this maximum radius r_c max could be defined with sufficient accuracy for a practical solution by equation 5.

$$r_{c\max} = \frac{d_c}{2 \tan(\alpha)} \quad (5)$$

A higher profile (pressure) angle α and a smaller hob major diameter d_c , results in a smaller spiral face gear minor diameter, achieved without concave flank undercut.

SPIRAL FACE COUPLINGS

A pair of spiral face gears can be used as a flange coupling (also known as Endicon® coupling [2]). Application of this type of coupling is similar to the Hirth and Curvic couplings. The Hirth coupling flange (Figure 5) has tapered, symmetrical teeth. Both mating flanges of the Hirth coupling have identical tooth geometry. The Curvic coupling flanges (Figure 6) have teeth with a circular tooth line, though the tooth flank profiles are straight. One flange of a coupling has concave tooth lines and the mating one has convex tooth lines.

A distinct difference of the involute spiral face coupling (Figure 6) is that the normal to the tooth line section tooth geometry and the normal load are the same at any radius. This results in even stress distribution and potentially greater load transmission capacity. Both mating flanges of the involute spiral face coupling have the same tooth geometry, but tooth spiral line directions have opposite clockwise and counterclockwise directions.

Spiral face gear parameter selection could be limited by a choice for




Figure 7: Sample of involute spiral face coupling assembly

manufacturing technology. For example, the minor diameter and pressure angle for a hobbled gear are limited by a condition per equation 3.

Figure 7 presents a sample of involute spiral face coupling assembly. Experimental involute spiral face coupling gear parameters are presented in Table 1.

SPIRAL FACE GEARS

A spiral face gear can be engaged with an involute helical pinion or worm at intersecting or crossed axes. Such engagement is used in the Helicon® type gears [3].

In order to avoid interference of the helical pinion tooth (worm thread) tip with the spiral face gear tooth tip at its

LUREN

PRECISION CO., LTD.



LFG-3540 Horizontal Gear Grinder






Luren LFG-3540 CNC Profile Grinding Machine for Gear Class AGMA 14

Luren LFG-3540 applies the most advanced technologies available around the globe, such as Fanuc CNC controller 32i, direct drive motor, linear motor, Windows 7-based operating system, Heidenhain linear optical scale, automatic stock dividing, on-board inspection, and rotary diamond dresser to easily achieve AGMA 14 with the touch of your fingertips.



Our Gear Cutting Tools

- Hobs
- Shaper Cutters
- Master Gears

Corporate Headquarters

Luren Precision Co., Ltd.
No.1-1, Li-Hsin 1st Road,
Hsinchu City, Taiwan, 30078
Phone : +886-3-578-6767
Email : sales@luren.com.tw
Website : www.luren.com.tw

North American Headquarters

Luren Precision Chicago Co., Ltd.
707 Remington Road, Suite 1,
Schaumburg, IL 60173, U.S.A.
Phone : 1-847-882-1388
Email : sales@lurenusa.com
Website : lurenusa.com





Figure 8: Sample of spiral face gear pair




Figure 9: Asymmetric tooth hobs – a) helical pinion, b) spiral gear

concave flank, the pinion and spiral gear geometry must satisfy to the condition (3). This condition requires a high pressure angle in in mesh with the spiral face gear tooth concave flank and the mating helical pinion flank. At the same time the effective tooth height in the gear mesh must provide a contact ratio greater than 1.0. In most cases both these conditions

cannot be satisfied with symmetric tooth profile in the normal section that is used for spiral face couplings. Application of

an asymmetric gear tooth profiles with high pressure angle for the concave flank and low pressure angle for the convex flank of the



GEARING AHEAD TO MEET INDUSTRY'S DEMAND FOR PRECISION

--Serving--

**Aircraft • Aerospace • Actuation
Instrumentation • Optic
Robotics • Radar • Medical
Marine • Defense • Experimental
Prototype • Production
Hi-Performance Automotive**



Precision Gear Products (up to AGMA Q14):
Spur Gears, Helical Gears, Worm Gears, Anti-Backlash Gears, Cluster Gears, Clutch Gears, Face Gears, Planetary Gears, Gear Assemblies, Gear Boxes, Bevel Gears, Miter Gears, Metric Gears, Internal Gears, Idler Gears, Gear Rack & Pinion, Worms, Wormshafts, Splines, Spline Shafts, Serrated Shafts.

STD Precision Gear & Instrument, Inc.
318 Manley St. Unit 5 • West Bridgewater, MA 02379
(888) STD-GEAR or (508) 580-0035
Fax (888) FAX-4STD or (508) 580-0071
E-mail info@stdgear.com
Web site: www.stdgear.com

"Your Open-Gearing Source for Over 60 Years"



P & G Machine & Supply Co., Inc.
2017 Old Shell Rd. • Mobile, AL 36607

- ◆ Made To Order Gears & Sprockets
- ◆ 24 Hour Emergency Service
- ◆ Quality Work/On Time Delivery

— Capabilities —
Helical • Spur • Worm Gears & Sprockets
Up To 72" in Diameter.



877-471-4481

Fax: 251-471-4485 • Web Site: www.pggears.com

Gear	Pinion	Spiral Face Gear
Number of Teeth	5	26
Normal Module, mm	0.85	0.85
Normal Drive Flank Pressure Angle	45°	45° (concave flank)
Normal Coast Flank Pressure Angle	10°	10° (convex flank)
Helix/Spiral Angle	57.9°	32.0°
Helix /Spiral Hand	LEFT	RIGHT
Pitch Diameter (PD), mm	9.600	29.068
Base Diameter, mm	4.504/9.111*	24.650
Major Diameter, mm	11.00	36.00
Minor Diameter, mm	7.74	28.00
Addendum, mm	0.70	0.70
Whole Depth, mm	2.00	2.00
Normal Tooth Thickness at PD, mm	1.270	1.270
Face Width, mm	10.00	4.00
Center Distance, mm	6.350±0.025	
Contact Ratio	1.05/2.60*	

Table 2. Spiral face gear data *drive/coast flank

spiral face gear allows a contact ratio greater than 1.0 in both flank gear meshes. A sample of the spiral face gear pair and its data are shown in Figure 8 and Table 2 accordingly. Asymmetric tooth hobs for the helical pinion and spiral face gear are shown in Figure 9.

POTENTIAL APPLICATIONS

Spiral face couplings have greater load capacity and utilize cost effective hobbing fabrication methods in comparison to the Hirth and Curvic type flange couplings. They may find many application areas including aerospace, automotive, agriculture, robotics, etc. For example, this type of coupling could be used to connect an airplane propeller to an engine shaft.

Spiral face gears that utilize convex-concave tooth contact at a high-pressure angle on drive tooth flanks have potentially greater load capacity in comparison to conventional face gears.

This makes it suitable for different power drives and actuators, and also in positioning systems for many industries and applications.

SUMMARY

- Geometry of involute spiral face gears and their tooth machining technology are described.
- Spiral face couplings and spiral face gears are described.
- Potential applications of spiral face couplings and spiral face gears are suggested. ☐

REFERENCES

1. Kapelevich, A.L., Direct Gear Design, CRC Press, 2013.
2. <http://www.itwheartland.com/endicon/C2AE-couplings/>.
3. Paul, DuWayne, Spiroid® And Helicon® Gearing, <http://itw.njolson.net/Spiroid/> Springer Encyclopedia of Tribology Article-Spiroid Gearing.pdf.

ABOUT THE AUTHOR: Dr. Alexander L. Kapelevich is the founder and president of the consulting firm AKGears, LLC—a developer of modern Direct Gear Design® methodology and software. He has over 30 years of experience in custom gear transmission development, and he is the author of “Direct Gear Design” and many technical articles. Kapelevich can be reached by e-mail at ak@akgears.com. Stephen D. Korosec is the president of Koro Ind. Inc., and he has been a manufacturer of fine and medium pitch precision gears for more than 40 years. He has extensive knowledge of tooling, production methods, and other techniques required to manufacture these high quality products. Korosec can be reached by email at steve@koroind.com.

FREE
ROUGH MACHINING ON
ALL FORGED PARTS

SEAMLESS

ROLLED RINGS

216" max.
O.D.

6" min.
O.D.

Up To
55,000 lbs

TOOL STEEL
STAINLESS - ALLOY
NICKEL - CARBON
ALUMINUM - COPPER

ISO9001:2008/AS/EN9100:2009C

All Metals & Forge Group

OPEN DIE FORGINGS & SEAMLESS ROLLED RINGS

800.600.9290
SteelForge.com